

# PATLED<sup>®</sup>s. See more in more ways



## CLN LED SPOT LIGHT

Thin and Compact with High Intensity

- Water, oil, coolant resistant
- Tilt and pan-tilt bracket options
- Concentrated, focused light for general task lighting applications

## CLK LED LIGHT BAR

Rugged Design; Built to Withstand Harsh Conditions

- High water, oil, chemical resistance; IP69k options
- Flexible body/lens options available
- M12 quick disconnect with Daisy Link compatibility
- Available lengths - 200mm, 300mm, 600mm



## CWK LED LIGHT BAR

Compact and Durable with Broad Coverage

- Redesigned lens for wide-angled illuminance
- Oil resistant side cable
- Available lengths - 200mm, 300mm, 600mm



## CLA LED LIGHT BAR

Ideal for High-pressure, High-temperature Washdown

- IP69k protection rating
- Diffusion lens type, great for vision systems
- Flexible mounting bracket options
- Available in 7 lengths - 100mm to 1500mm



## CWA LED LIGHT BAR

## CWA LED LIGHT BAR

Bright and Affordable

- Great as a fluorescent lighting replacement
- Clear lens type for brighter direct lighting
- Available lengths - 300mm, 600mm, 900mm



**ECOLAB<sup>®</sup>**



	CLK	CWK	CLA	CWA	CLN
<b>PRIMARY APPLICATION</b>	MACHINE TOOLING, EQUIPMENT LIGHTING, FOOD, MEDICINE, CHEMICAL	MACHINE TOOLING, EQUIPMENT LIGHTING	FOOD PROCESSING, BEVERAGE PROCESSING, PHARMACEUTICAL, PRINTING PRESS, AUTOMATION	COST EFFICIENT LIGHTING CONTROL PANEL LIGHTING ELEC. SYSTEM INTEGRATION PANEL SHOPS	MACHINE TOOLING, CONTROL PANEL, FOOD PROCESSING, BEVERAGE PROCESSING, PHARMACEUTICALS, ASSEMBLY LINES
<b>EXTRA DESCRIPTION</b>	FOCUSED LIGHT, ROBUST	WIDE DIFFUSED LIGHT, ROBUST	EMITS LOW HEAT, ENERGY EFFICIENT	EMITS LOW HEAT, ENERGY EFFICIENT	EXTREMELY THIN, 2.2MM WIDTH, WITH WIDE RANGE OF MOTION
<b>SIZES</b>	200,300,600 MM	200,300,600 MM	100,200,300,600,900, 1200 MM	300,600,900 MM	85 MM
<b>ENVIRONMENT RATING</b>	IP66G/67G/69K	IP66G/67G	IP66/67/69K	IP65	IP66G/67G/69K
<b>ENVIRONMENT</b>	WATER AND OIL RESISTANT, CHEMICAL RESISTANT, HIGH TEMPERATURE, HIGH PRESSURE WASHDOWN	WATER AND OIL RESISTANT	HIGH TEMPERATURE, HIGH PRESSURE WASHDOWN	DUST TIGHT, PROTECTION AGAINST HEAVY SEAS	WATER AND OIL RESISTANT, CHEMICAL RESISTANT, HIGH TEMPERATURE, HIGH PRESSURE WASHDOWN
<b>HOUSING</b>	ALUMINUM ALLOY OR STAINLESS STEEL	ALUMINUM ALLOY	POLYCARBONATE RESIN	POLYCARBONATE RESIN	ALUMINUM ALLOY
<b>WINDOW</b>	TEMPERED OR ACRYLIC GLASS	TEMPERED GLASS	POLYCARBONATE RESIN	POLYCARBONATE RESIN	TEMPERED GLASS
<b>CERTIFICATIONS</b>	UL, CUL, CE, ROHS	UL, CUL, CE, ROHS	UL, CUL, CE, ROHS	UL, CUL, CE, ROHS	UL, CUL, CE, ROHS
<b>VOLTAGE</b>	24 VDC	24 VDC	24 VDC	24 VDC	24 VDC
<b>OPERATING TEMPERATURE RANGE</b>	-40°C TO 60°C	-10°C TO 50°C	-40°C TO 60°C	-30°C TO 60°C	-40°C TO 60°C
<b>MOUNTING OPTIONS</b>	DIRECT, FLUSH AND SWIVEL WITH OPTIONAL BRACKET	DIRECT, FLUSH AND SWIVEL WITH OPTIONAL BRACKET	SCREW MOUNT, MAGNETIC MOUNT	SCREW MOUNT	DIRECT, PAN & TILT BRACKET
<b>LUMENS</b>	865 - 2600 LM	800-2400 LM	60-1725 LM	350-1050 LM	550 LM
<b>LIGHTING COLOR OPTIONS</b>	DAYLIGHT WHITE	DAYLIGHT WHITE	DAYLIGHT WHITE	DAYLIGHT WHITE	DAYLIGHT WHITE
<b>LIGHTING TEMPERATURE</b>	6500K	6500K	6800K	6500K	6500K
<b>CABLE</b>	SIDE EXITING, M12, DAISYLINK	SIDE EXITING	SIDE EXITING	SIDE EXITING	SIDE EXITING
<b>VIBRATION RESISTANCE</b>	19.6 M/S <sup>2</sup>	20 M/S <sup>2</sup>	19.6 M/S <sup>2</sup>	19.6 M/S <sup>2</sup>	19.6 M/S <sup>2</sup>

## PATLITE®

New Frontiers in Safety, Security and Comfort.

**PATLITE (U.S.A.) Corporation**  
 20130 S. Western Ave. Torrance, CA 90501, U.S.A.  
 TEL:1-310-328-3222 FAX:1-310-328-2676 EMAIL:sales@patlite.com

**PATLITE (SINGAPORE) PTE LTD**  
 No.2 Leng Kee Road, #05-01 The Hong Centre, Singapore 159086  
 TEL:65-6226-1111 FAX:65-6324-1411 EMAIL:sales@patlite.com.sg

**PATLITE Europe GmbH**  
 Am Soeldnermoos 8, D-85399 Hallbergmoos, Germany  
 TEL:49-811-9981-9770-0 FAX:49-811-9981-9770-9 EMAIL:info@patlite.eu

**PATLITE (CHINA) Corporation**  
 Room 1102-1103, No.55, Lane 777, Guangzhong Road (West),  
 Zhabei District, Shanghai, China 200072  
 TEL: +86-21-6630-8969 FAX: +86-21-6630-8938 EMAIL: sales@patlite.cn

**PATLITE KOREA CO., LTD.**  
 A-2603, Daesung D-POJIS, 543-1 Gasan-dong, Geumcheon-gu, Seoul, Korea  
 TEL: +82-2-523-6636 FAX: +82-2-523-6637 EMAIL: sales@patlite.co.kr

**PATLITE Corporation Head Office**  
 4-4-25, Hommachi, Chou-ku, Osaka-shi, 541-0053 Japan  
 International Sales Division  
 TEL: +81-6-7711-8953 FAX: +81-6-7711-8961 EMAIL: overseas@patlite.co.jp

**PATLITE Japan Representative Office in Taiwan**  
 7F, No. 91, Huayin St, Datong District Taipei, Taiwan R.O.C  
 TEL: +02-2555-1611 FAX: +02-2555-1621 EMAIL: info@patlite.tw

### CAUTION

To ensure correct use of these products, read the Instruction Manual prior to use. Failure to follow all safeguards can result in fire, electric shock, or other accidents. Specifications are subject to change without notice.