



**Ecolab Deutschland GmbH
P.O. Box 13 04 06
D-40554 Düsseldorf**

certifies that for

**PATLITE Europe GmbH
Am Soeldnermoos 8
D-85399 Halbergmoos**

material resistance tests

were performed with cleaning substances **P3-topactive OKTO**, **P3-topactive 200**, **P3-topax 56** and demineralized water as a zero reference factor.

The material resistance of the tested

PATLITE LED Light Bar CLA-Serie

to the P3 products used in the test can be considered to be positive according to the cleaning procedure mentioned overleaf.

Düsseldorf, 25th march 2011

Ecolab Deutschland GmbH

i.V.


Thomas Tyborski

i. V.


Reimund Laaff

This certificate is based on:

- documented test procedures (test no.: F&E/P3-E Nr. 40-1) according to material resistance
- defined product descriptions
- standardized cleaning procedure

Test procedure Ecolab-test F&E Nr. 40-1

Dipping test:

- Complete immersion in solutions/liquid

Test period:

- 28 days / reference "water": 14 days

Temperature:

- room temperature (constant)

Analysis:

- Visual judgement like swelling, brittleness, discoloring
- compared to zero-reference factor (demineralized water)
- Photo documentation

Product specifications:

P3-topactive OKTO

Acid disinfectant based on peroxyacids for the food and beverage industry

P3-topactive 200

Alkaline, chlorine-free foam cleaner for the food and beverage industry

P3-topax 56:

Acid foam cleaning substance for the food and beverage industry

Cleaning plan for food and beverage industry*



Rinsing with water 40 – 50°C

Rinsing with low pressure. Rinsing from top to bottom in the direction of the drains. Cleaning of the drains.



Foaming from bottom to top

alkaline: P3-topactive 200 2 – 5 % daily

acid: P3-topax 56 2 % on demand

temperature: cold up to 40°C

contact time: 15 min. recommended



Rinsing with water 40 – 50°C

Rinsing from top to bottom with low pressure

Disinfection : P3-topactive OKTO 1-3 %, 10-30 min

*short description