

# SPECIFICATIONS

生産終了  
Production end

Model		RS-12	RS-24
Rated Voltage		12V DC	24V DC
Operating Voltage		9V to 16V DC	20 to 30V DC
Current Consumption		500mA	300mA
Power Consumption		6.0W	7.2W
Flashing Rate		120 Flashes Per Minute	
Operating Temperature Range (Relative Humidity)		- 30°C to + 80°C (Less than 90%)	
Mounting	Location	Indoor & Outdoor Use	
	Direction	Indoor: Upright, Inverted & Sideways    Outdoor: Upright Only	
Protection Rating		IP23 (IP55 with optional rubber gasket SZ-210)	
Vibration Resistance		44.1m／s <sup>2</sup> (33Hz, Back and Forth:2h · Right to Left:2h · Up and Down:2h)	
Insulation Resistance			
Withstanding Voltage			
Buzzer	Sound Level		
	Tone		
Bulb	Rating	12V 6W	24V 6W
	Base/Bulb	BA9S / G14	
Luminous Intensity		700cd    without dome	
Mass (Tolerance ±10%)		0.4kg	
No.RS-12-PDFD-EN-1_2			
<div>●This product conforms to the CE requirements and shows the CE Marking.</div>			
<div>PATLITE Corporation</div>			