
## **SPECIFICATIONS**

[General Specifications]

	[Ochoral Opcomoditorio]	
Model	SKHE-100	SKHE-200
Rated Voltage	100V AC (50/60Hz)	200V AC (50/60Hz)
Operating Voltage Range	Rated Voltage ±10%	
Rated Current Consumption	0.044 A or less	0.022 A or less
Rated Power Consumption	4 W	
Operating Ambient Temperature	- 10 °C to + 50 °C	
Operating Ambient Humidity	Less than 90 % (No condensation)	
Storage Ambient Temperature	- 10 °C to + 50 °C	
Storage Ambient Humidity	Less than 90 % (No condensation)	
Mounting Location	Indoors and Outdoors	
Mounting Direction	[Indoors] Upright ,Inverted and Sideways / [Outdoors] Upright	
Protection Rating	IP23 (IEC 60529)	
Environmental Condition	Upright only	
	45 m/s² (JIS D 1601-1995)	
Vibration Resistance		
Insulation Resistance	More than 1M $\Omega$ at 500VDC between the terminals and the chassis	
Withstand Voltage		terminals and chassis without breaking insulation
	1000V AC	1500V AC
Flashing Rate	120 ± 25 Flashes Per Minute	
Luminous Intensity	Red: 3000 cd or more / Amber: 3000 cd or more	
	Green: 2500 cd or more / Blue: 2000 cd or more	
Mass (Tolerance ±10%)	0.6 kg	
Outer Dimensions	Refer to the Outer Dimension Drawing	
Remarks	There are no contents of controlled substances exceeding the threshold for the RoHS Directive.	

## [Model Number Configuration]




No. SKHE-100-W18E-1\_2

## **PATLITE** Corporation

Production end

PATLITE Corporation
SKHE-100-W18E-2\_2



From Wire Exit 310±30